



• **WATER SUPPLY**  
SYSTEM DESIGN

RAINFINE (DALIAN) IRRIGATION CO., LTD.



• WATER SUPPLY  
SYSTEM DESIGN

RAINFINE (DALIAN) IRRIGATION CO., LTD.

# Ethiopia Omo river 2500ha irrigation project design based on center pivot irrigation system

Rainfine Irrigation Design Institute  
Dalian China



• WATER SUPPLY  
SYSTEM DESIGN

RAINFINE (DALIAN) IRRIGATION CO., LTD.

# Catalog

1. Guide line of the design
2. The secret discovered
3. Water intake from the main river
4. Pivot machine design for irrigation areas
5. Ditches and pump station

## 1. Guide line of the design:

- (1). Taking in water from the nearest ditches into the irrigation area.
- (2). Constructing the ditches, restraint gate, pump station and pipelines and other facilities for the three irrigation areas.
- (3). Using the natural riverbed to reduce the investment cost of ditches.
- (4). Two shift working of the center pivot irrigation machines can minimize the water pipes diameter and the total flow of the pump station.



## 2. The secret discovered

Near the irrigation area, there is a dry river (Hereinafter referred to as River V) which is formed by rains and floods in rainy season.

A natural ditch can be built by drawing water into River V from Point B. So it can save more costs in building ditches.

Leveling the riverbed and led water from main river to V river.

Google earth





## 2.1 Drawing water schematic diagram 1

Contour map of River V:

It is feasible to drawing water from river based on the height difference between the water entrance of River V and the artificial ditches. But Point B is an obstacle will impede water flows into the River V.




## 2.2 Drawing water schematic diagram 2




The red selected area in right scheme is the contour map of the left map. It shows B is the highest point. (Elevation 384m)

Drawing water into River V by punching through out Point B.




## 2.3 Drawing water into the V riverbed




## 2.4 Drawing water into the artificial ditches



The below scheme is the contour map of the left map. It shows that there is a slope(white line) blocking the water between River V and artificial ditches. (Elevation 380m)






## • WATER SUPPLY SYSTEM DESIGN

RAINFINE (DALIAN) IRRIGATION CO., LTD.

### 2.5 Drawing water into the artificial ditches

We can build a restraint valve at this slope for controling the flow and also preventing the flood.





## • WATER SUPPLY SYSTEM DESIGN


RAINFINE (DALIAN) IRRIGATION CO., LTD.

### 2.6 Drawing water into the artificial ditches

There are two artificial ditches, the first one supplies water for the NO. 1 and 2 irrigation areas and the other supplies for No.3 irrigation area.

It is very favorable for building ditches in this area based on the topography. And if necessary, the booster pump can be used. Booster pump is cheaper than ordinary pump station.






## 2.7 Drawing water into the artificial ditches



## 2.8 Floods discharge in rainy season



Drainage is needed for preventing damage caused by the floods.

The contour map shows the left side (green line) elevation is 375m and the right side (red line) is 373m. If we build a restrict gate in white line, it will control the flood in rainy season.



## 2.9 Floods discharge in rainy season



Elevation of red area is 378m. It will be under the waterline in rainy season and over the waterline in dry season. This can discharge water in rainy season and store water in dry season.



### 3. Water intake from main river



The picture shows the water intake from main river.

Water can be led from here into the artificial ditches from rivers.



### 3.1 Restraint gate

The restraint gate at the entry of artificial ditch can control the water volume effectively.

### 3.2 Restraint gate

When the water level is going up, the tank rise up and the other end get down to close the gate a little .

When the water level is getting down, the tank goes down and the other end get up to open the gate a little. In this way the water flow quantity can be controlled.

When the big flood comes, the main valve in the gate can be closed to stop the water.



2010/10/27 15:32

Rainfine products

### 3.3 Restraint gate

The water flow into the main artificial ditches through the restraint gate and flow to the pump station.

2010/10/27 15:30

Rainfine products

### 3.4 Artificial ditches

Water flow speed is reduced in the ditches, The sand and dirty will sink on the bottom of ditch. Only clean water can flow further to the pump station 2000m away.



2010/10/27 15:38


Rainfine products


# WATER SUPPLY SYSTEM DESIGN

RAINFINE (DALIAN) IRRIGATION CO., LTD.

## 4. Pivot machine design for irrigation areas

The pivots works in 2 shift,  
This idea can reduce the  
diameter of the water pipes  
and the size of the pump  
station. By our calculation, the  
total water requirement for this  
area is 5228m<sup>3</sup>/hr





## 4.1 No.1 irrigation area

9 pivots in all, 7 of them cover 136ha each, 2 cover 55ha each, Total coverage: 1062ha.  
Total water demand:  
2032m<sup>3</sup>/hr


No.1 pump station is built in the center of the irrigation area.

This design can reduce water supply volume and the size of the water pipes, it can also lower the pressure losses and thus reduce the pump power and lower energy costs.


## 4.2 No.1 irrigation area

No.1 irrigation area is divided into two regions, west and east regions, by two shift working of the irrigate machine, the investment of the pump station can be much more reduced.

West (1-1/1-2/1-3/1-4/1-5)



East(1-6/1-7/1-8/1-9)



## 4.3 No.1 irrigation area


No.1 pump station is built beside the artificial ditches with a water reservoir under it. So the water can be pumped directly.

Pump station No.1



# WATER SUPPLY SYSTEM DESIGN

RAINFINE (DALIAN) IRRIGATION CO., LTD.



## 4.4 No.2 irrigation area

6 pivots in all, 4 of them cover 136ha each, 1 covers 55ha, 1 covers 109ha

Total coverage: 708ha

Total water demand:  
1424m<sup>3</sup>/hr


No.2 pump station is built in the center of the irrigation area.

This design can reduce water supply volume and the size of the water pipes, it can also lower the pressure losses and thus reduce the pump power and lower energy costs.


## 4.5. No.2 irrigation area

No.2 irrigation area is divided into two regions, west and east regions, by pump station and irrigate in proper order. This divide can reduce the investment of the pump station.

West (2-1/2-2/2-3)




East(2-4/2-5/2-6)




## 4.6 No.2 irrigation area

No.1 pump station is built beside the artificial ditches with a water reservoir under it. So the water can be pumped directly.

Pump station No.2



RAINFINE (DALIAN) IRRIGATION CO., LTD.



## 4.7 No.3 irrigation area

8 pivots in this area, 6 of them cover 136ha each, 1 covers 41.5ha, 1 covers 66.2ha  
Total coverage: 924ha


Total water demand: 1772m<sup>3</sup>/hr  
No.3 pump station is built in the center of the irrigation area.

This design can reduce water supply volume and the size of the water pipes, it can also lower the pressure losses and thus reduce the pump power and lower energy costs.


## 4.8 No.3 irrigation area

No.2 irrigation area is divided into two regions, north and south regions. The pivot can work in two shift.

South (3-1/3-2/3-3/3-4)



North(3-5/3-6/3-7/3-8)





## 4.9 No.3 irrigation area

No.3 pump station is built beside the artificial ditches with a dam under it. So the water can be pumped directly.

Pump station No.3



## 5. Ditches and pump station

The picture shows the water conservation project .

The area in this picture is similar to our project, both of them are drawing water into the artificial ditches from natural rivers, then pumping to all the irrigation areas.

## 5.1 Pump station

Filtration systems

Water pumps

Power supply systems

Water hammer protection system



## 5.2 Ditches to pump station

Water dam under the pump station.  
Outside the entrance of the pump is  
equipped with filters.

Water dam can provide sufficient water.

There is a ladder on the top  
of pump station is for the  
maintenance workers to  
clean-up the filters.

2010/10/27 15:49



2010/10/27 15:50

Rainfine products

## 5.3 Water hammer protection system

This is the water hammer protection system for the pump station to work against electric power failure or other accident.



2010/10/27 15:51

Rainfine products



• **WATER SUPPLY**  
SYSTEM DESIGN

RAINFINE (DALIAN) IRRIGATION CO., LTD.

Thank you for your attention

Tel:+86-411-82731882

Fax:+86-411-82723748

Cell phone:+86-139-4097-2553

<http://www.centerpivotchina.com>